

ViscoTwin 104 G10 TORQUE VALUES

1-25

3050 NPSH Optimized Pressure Sensor (Hex Head, 34mm)
15 Nm | 11.1 lb-ft

2180 Spindle Screw M16 (Hex Head, 36mm)
150 Nm | 110.6 lb-ft.

2527 Hex Head Cap Screw for Pump Face M16 (Hex Head, 24mm)
150 Nm | 110.6 lb-ft

2532 Hex Head Cap Screw for Seal Housing M6 (Hex Head, 10mm)
6 Nm | 4.42 lb-ft

2259 Socket Head Cap Screw for Seal Housing M6 (Socket Hex Nut, 5mm)
7.5 Nm | 5.53 lb-ft

1016 Hex Head Cap Screw for Pump Housing M16 (Hex Head, 24mm)
150 Nm | 110.6 lb-ft

3037 Set Screw for Red O 3/8" (Hex Screw, 3/16")
4 Nm | 2.95 lb-ft

3035 Countersunk Socket Head Bolt for Red O M6 (Hex Socket Head, 4mm)
4 Nm | 2.95 lb-ft

Set with 100 Nm, then loosen it and set it again with 50 Nm.
1526 Shaft nut M35 (Groove Nut)
100 Nm | 73.7 lb-ft
50 Nm | 36.9 lb-ft

2258 Hex Head Cap Screw for Gear Housing M16 (Hex Head, 24mm)
150 Nm | 110.6 lb-ft

3002 Cap Nut for Lantern Safety Guard M5 (Hex Cap Nut, 8mm)
3 Nm | 2.22 lb-ft

2233 Magnetic Screw Plug B.S.P.P. 3/4" (Hex Head, 30mm)
15 Nm | 11.1 lb-ft

3100 Gapping Port Cover (Hex Head, 24mm)
15 Nm | 11.1 lb-ft

2360 Oil Level Sight Gauge B.S.P.P. 3/4" (Hex Head, 32mm)
15 Nm | 11.1 lb-ft

2177 Hex Head Cap Screw for Driven Shaft M16 (Hex Head, 24mm)
200 Nm | 147.5 lb-ft

2186 Socket Head Cap Screw for Gear Wheel M5 (Hex Socket Head, 5mm)
17 Nm | 12.5 lb-ft

(1526) Grub Screw M6 (Hex Screw, 3mm)
8 Nm | 5.9 lb-ft

1008 Socket Head Cap Screw for Bearing Cover M8 (Hex Socket Head, 6mm)
20 Nm | 14.7 lb-ft

2250 Grub Screw for Drive/Pump Coupler 3/8" (Hex Screw, 3/16")
16 Nm | 11.8 lb-ft

2525 Hex Head Cap Screw for Lantern M16 (Hex Socket Head, 12mm)
150 Nm | 110.6 lb-ft

(Varies depending on Drive)

